

## TEKNISKE DATA

## Egenskaper

## Norm

## Enhet

Granito <sup>PRO</sup>Granito Artigo Granito 

Gummi gulvbelegg med 'chips'. Slett overflate.

Leveres i rull og flis.



  
COVERING THE WORLD

## Polyflor Nordic


Kjelsåsveien 168 B

0884 OSLO

Tel.: 23 00 84 00

Fax: 23 00 84 10

[firmapost@polyflor.no](mailto:firmapost@polyflor.no)[www.polyflor.no](http://www.polyflor.no)

Type	EN 1817		
Overflate			
Mønster			Chips
Farger			20
Totalvekt	EN 430	g/m <sup>2</sup>	3.300
Klassifisering	EN 685		23, 34, 42
Totaltykkelse	EN 428	mm	2,0
Format rull	EN 426	m / m <sup>2</sup>	1,9 x 14 / 26,6 m <sup>2</sup>
Format fliser	EN 427	cm / m <sup>2</sup>	61 x 61cm / 8,93 m <sup>2</sup>
Restinntrykk	EN 433	mm	0,05
Slitasjetest	ISO 4649 Met.A-5N	mm <sup>3</sup>	150
Dimensjonsstabilitet	EN 434	%	± 0,30
Brann	EN 13501-1		B <sub>fl</sub> -sl
Friksjon	DIN 51130		≥6 (R9)
Trinnlyd	ISO 140 - 8	dB	6
Hardhet	ISO 7619 ≥ 75 shore A		88 ± 5
Elektrisk oppladning	EN 1815	kV	≤ 2 (antistatisk)
El. Motstand	IEC 60093	Ohm	>10 <sup>10</sup>
Kjemikaliebestandighet	EN 423		ja*
Rullestol	EN 425		Ja (W hjul)
Varmekabler			ja, ikke over 27°C

\*Motstandsdyktig. Ved lengre tids påvirkning eventuelt høy konsentrasjon, vennligst ta kontakt