

TEKNISKE DATA

Egenskaper

Norm

Enhet

Harmony fx PUR

Harmony fx PUR

Heterogen PVC

Unimønstret , 2,0mm i følgende farger:

6411 – 6414 – 6415 – 6416

6419 – 6420 – 6421 – 6426

Leveres i rull.



100% RESIRKULERBAR



Polyflor Nordic

Kjelsåsveien 168 B

0884 OSLO

Tel.: 23 00 84 00

Fax: 23 00 84 10

firmapost@polyflor.no

www.polyflor.no

Type	EN 649		Heterogen PVC
Overflate			PUR
Mønster			Ensfarget
Farger			8
Totalvekt	EN 430	g/m ²	2.700
Klassifisering	EN 649		23, 34, 43
Totaltykkelse	EN 428	mm	2,0
Slitesjikt	EN 429	mm	0,7
Format rull	EN 426	m	2 m x 20 m / 40 m ²
Restinntrykk	EN 433	mm	< 0,1
Lysekthet	ISO 105-B02 Metode 3		≥ 6
Brann	EN 13501-1		Bfl – S1
Friksjon	AS/NZS 4586 DIN 51130 EN 13893		R10 R10 DS
Trinnlyd	ISO 717/2	dB	-
Elektrisk oppladning	EN 1815	kV	< 2 (antistatisk)
El. motstand	EN 1081	Ohm	-
Kjemikaliebestandighet	EN 423		*
Slitasjegruppe	EN 649		T
Varmekabler			Ja, ikke over 27°C
Trinsestolfast	EN 425		Ja, type W, EN 12529

* Motstandsdyktig. Ved lengre tids påvirkning eventuelt høy konsentrasjon, vennligst ta kontakt.