



# POLYSAFE Wood fx Acoustic PUR

## TEKNISKE DATA

### Egenskaper

### Norm

### Enhet

### Polysafe Wood fx Acoustic PUR

## POLYSAFE Wood fx Acoustic PUR

Sklisikker heterogen PVC, tremønster.  
Trinnlydsdempende.

Leveres i rull.



100%  
RESIRKULERBAR



**Polyflor Nordic**  
Kjelsåsveien 168 B  
0884 OSLO  
Tel.: 23 00 84 00  
Fax: 23 00 84 10  
[firmapost@polyflor.no](mailto:firmapost@polyflor.no)  
[www.polyflor.no](http://www.polyflor.no)

Type	EN 651		Heterogen PVC
Overflate			
Mønster			Tremønster
Farger			8
Totalvekt	EN 430	g/m <sup>2</sup>	3.000
Klassifisering	EN 13845		23, 34, 42
Totaltykkelse	EN 428	mm	3,7
Format rull	EN 426	m	2 m x 20 m / 40 m <sup>2</sup>
Format fliser	-	mm / m <sup>2</sup>	-
Slitesjikt		mm	0,65
Brann	EN 13501-1		Bfl – S1
Friksjon	AS/NZS 4586 RRL Pendium test	≥36	R10 ≥36 (våt test)
Trinnlyd	EN ISO 140-8	dB	≥19dB
Emisjon	AgBB Voc test		Ja
Elektrisk oppladning	EN 1815	kV	<2kV - antistatisk
Kjemikaliebestandighet	EN 423		*
Slitasjegruppe	EN 649		T
Varmekabler			ja, ikke over 27°C

\* Motstandsdyktig. Ved lengre tids påvirkning, eventuelt høy konsentrasjon, vennligst ta kontakt.